



Kuriyama Hydraulic

Connections™

HOT OILER HOSE BY **ALFAGOMMA®**



Kuriyama of America, Inc.

Headquarters, Sales Office and Warehouse Location

360 E. State Parkway • Schaumburg, IL 60173-5335

Phone: (847) 755-0360 • Toll-free FAX: (800) 800-0320 • International FAX: (847) 885-0996

Web Site: www.kuriyama.com

Orders: customerservice@kuriyama.com

Visit us
www.kuriyama.com
on the Web!



SOUTHWEST WAREHOUSE
KURIYAMA OF AMERICA, INC.
HOUSTON
200 PORTWALL ST., SUITE 100
HOUSTON, TX 77089
Phone: (713) 674-8212
Toll Free Phone: (800) 501-6808
FAX: (713) 674-5214
Toll Free FAX: (800) 800-5214
Orders: hocustomerservice@kuriyama.com

WESTERN WAREHOUSE
KURIYAMA OF AMERICA, INC.
SANTA FE SPRINGS
10749 SHOEMAKER AVE.
SANTA FE SPRINGS, CA 90670-4039
Phone: (562) 941-4507
FAX: (562) 941-8940
Toll Free FAX: (800) 326-8940
Orders: sfscustomerservice@kuriyama.com

SOUTHEAST WAREHOUSE
FORTNEY SALES CO., INC.
4221 CANTRELL ROAD NW
ACWORTH, GA 30101
Phone: (770) 427-6528
FAX: (770) 423-9249
Toll Free FAX: (800) 423-9249
Web Site: www.fortneysales.com
Orders: orders@fortneysales.com

EASTERN WAREHOUSE
EASTERN RUBBER & PLASTICS CO., INC.
100 GOLDMAN DR.
PLUMSTED INDUSTRIAL PARK
CREAM RIDGE, NJ 08514
Phone: (609) 758-0100
FAX: (609) 758-0102
Toll Free FAX: (800) 445-7138
Web Site: www.easternrubber.com
Orders: sales@easternrubber.com

IN MEXICO:

KURIYAMA DE MEXICO, S DE RL DE CV, AV JOSE PALOMO MARTINEZ NO 520-20, BODEGA 5, PARQUE INDUSTRIAL OMOLAP, APODACA, N.L. CP:66633, MEXICO

Telefonos: (81) 1086-1870 ó 71 • Lada sin Costo: 01-800-822-52-00 • FAX: (81) 1086-1869

Internet: www.kuriyama.com • Correo Electronico: ventas@kuriyama.com

The "Alfagomma" trademark contained in this publication is a registered trademark of Alfagomma S.p.A.

The trademarks contained in this publication are trademarks of Kuriyama of America, Inc.

KHCHOHFL0219

HOT OILER HOSE

ALFAGOMMA OILFIELD HOT OILER HOSE IS DESIGNED FOR HIGH PRESSURE TRANSFER OF HOT OIL AND PETROLEUM PRODUCTS IN APPLICATIONS TO 300°F AND 2400 PSI TO CLEAR PARAFFIN AROUND CASING, PIPING, TANKS AND TUBING TO HELP START THE FLOW OF OIL.

Alfagomma Hot Oiler Hose is compatible with hot oil and provides excellent high pressure service across multiple drill site applications. The hose construction resists crushing and kinking for durability, and features a **MINETUFF** cover that is resistant to abrasion, oil and weathering to provide maximum performance.

Alfagomma Hot Oiler Hose is qualified with **Series D (C124) permanent crimp couplings** for a safe and secure connection and provides robust service life in challenging applications.

MARKETS:

- Oil & Gas
- Construction
- General industrial

MEDIA:

- Hot oil
- Hot wax

HOT OILER - MINETUFF



General Applications:

Hot Oiler Hose is designed for high pressure transfer of hot oil and petroleum products.

Construction:

- **Tube:** oil resistant synthetic rubber.
- **Reinforcement:** two high tensile steel braids.
- **Cover:** abrasion, ozone and hydrocarbon resistant black synthetic rubber.

Service Temperature Range:

-40°F (-40°C) to +300°F (+150°C)

MSHA APPROVED

Safety factor: 3:1

Length: up to 200' (61 m)

Series Number	Dash	↔		↔		psi	Mpa	psi	Mpa	↷		lb/ft	kg/m
		in	mm	in	mm					in	mm		
TF2H0-24	24	1 1/2	38.0	1.96	49.90	2400	16.5	7200	49.5	16.93	430.0	1.33	1.970

